

SLA

READY TO START

Ready to use, SLA batteries (AGM technology) are Factory Activated, completely spill-proof, and require **no maintenance**. Our SLA offer is **the widest ready to use range** available on the market.



FACTORY ACTIVATED
AGM (Absorbent Glass Mat) technology.



READY TO USE
Just plug & play.



NO MAINTENANCE
VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN
Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING
Very safe.



HIGH STARTING POWER & EXTENDED CYCLE LIFE



SLA
FACTORY ACTIVATED

6V & 12V - TECHNICAL FEATURES

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BTZ7S	300635	6	6.3	130	113	70	105		A
BT7B-4	300641	6.5	6.8	110	150	65	93		A
BTZ7V	300912	6.5	6.8	105	113	70	121		A
BTZ8V	300890	7	7.4	120	113	70	130		A
BT9B-4	300642	8	8.4	120	150	68	105		A
BTZ10S	300636-1	8.6	9	190	150	88	93		A
BT12-10Z	300913	10	10.5	180	194	59	112		A
BTZ12S	300637-1	11	11.6	215	150	88	110		A
BT12B-4	300643	10	10.5	210	150	69	130		A
BTZ14S	300638-1	11.2	11.8	230	150	88	110		A
BT14B-4	300644	12	12.6	210	150	69	145		A
SLA 12-19	300632	17.7	19	235	182	77	168		A
BT4B-5	300756	2.3	2.4	40	113	38	85		J
BTR4A-5	300667	2.3	2.4	35	113	48	85		I
BTX4L+/BTZ5S	300669	4	4.2	65	113	70	85		A
BTX5L/BTZ6S	300670	5	5.3	90	113	70	105		A
BTX6.5L	300904	6.5	6.8	85	139	66	100		B
BTX7L	300673	6	6.3	100	113	70	130		A
BTX7A	300672	6	6.3	105	150	87	93		A
BTX9	300674	8	8.4	135	150	87	105		A
BT12A	300679	10	10.5	175	150	87	105		A
BTX12	300680	10	10.5	180	150	87	130		A
BTX14	300681	12	12.6	200	150	87	145		A
BTX14L	300760	12	12.6	200	150	87	145		A
BTX14AH/BB14-A2/B2	300758	14	14.7	210	135	90	164		A
BTX14AHL/BB14L-A2/B2	300759	14	14.7	210	135	90	164		D
BTX16	300763	14	14.7	230	150	87	161		A
BTX20CH	300766	18	18.9	270	150	87	161		A
BTX20H	300688	18	18.9	310	175	87	155		A
BTX20HL	300689	18	18.9	310	175	87	155		A
BTX24HL/B50-N18L-A/A2/A3	300770	21	22.1	350	205	87	162		A
BIX30L	300631	30	31.6	400	165	125	175		A
12N5.5-3B	300840	5.5	5.8	70	135	60	130		A
12N5.5-4A/4B	300841	5.5	5.8	70	135	60	130		A
BB3L-A/B	300842	3	3.2	35	98	56	110		A
BB4L-B	300665	4	4.2	50	120	70	92		B
BB5L-B	300671	5	5.3	65	120	60	130		A
BB7-A	300850	8	8.4	120	135	75	133		B
BB7C-A	300843	8	8.4	80	129	89	114		A
BB7L-B2	300836	8	8.4	100	135	75	133		E
BB9-B	300675	9	9.5	120	135	75	139		A
BB10L-A2/B2	300677	11	11.6	120	133	90	145		A
BB12AL-A2	300837	12	12.6	150	134	80	161		B
BB12A-A/B	300881	12	12.6	150	134	80	161		A
BB14A-A2	300838	14	14.7	210	134	88	176		B
BB16AL-A2	300839	16	16.8	160	205	70	162		A
BB16CL-B	300771	19	20	230	175	100	175		F
53030	300880	30	31.6	300	178	123	166		C
6N4-2A/A-4	300916	4	4.2	25	71	71	93		-
6N6-3B/B-1	300917	6	6.3	50	95	55	117		B
B49-6	300918	10	10.5	80	91	83	159		B
B38-6A	300919	13	13.7	105	119	83	161		B
6N11A-1B/3A	300915	11	11.6	90	121	58	130		B
6N11A-4A	300914	11	11.6	90	121	58	130		B

TERMINAL TYPE	A	B	C	D	E	F	G	H	I	J

www.bs-battery.com